



The Chemical Company

Technical Bulletin

25

Traffic
Coatings

Carpeting over MasterSeal® Traffic 1500

FORMERLY CARPETING OVER SONOGUARD®

Occasionally owners of a new MasterSeal Traffic 1500 Pedestrian System may wish to have it carpeted over. We have concerns because a typical carpet could become soaked during rain and hold moisture against MasterSeal Traffic 1500. This condition is similar to immersion of MasterSeal Traffic 1500, which is not recommended.

One solution is to occasionally remove the carpet, allowing MasterSeal Traffic 1500 to dry out. Another is to use a product called Coverdeck, by Coverdeck Systems of Wilmington, DE. This is a system of modular interlocking carpet tiles for interior and exterior use. Coverdeck tiles have a pattern of small "feet" on the bottom which raise the carpet off the surface, allowing for air circulation and drainage.

MasterSeal Traffic 1500 system (MasterSeal M 200 and MasterSeal TC 225 used together) was tested in our R & D Laboratory according to ASTM D4833 to verify that the small "feet" of the Coverdeck tiles would cause no damage to MasterSeal. Test results were positive and Coverdeck products were approved for use with MasterSeal.

Additionally, since Coverdeck provides adequate clearance for airflow above the MasterSeal, we do not object to Coverdeck remaining on MasterSeal Traffic 1500 year-round. If you have any other questions, please contact us.

Coverdeck Systems may be reached by calling 800-550-3325 or visiting their website at www.coverdeck.com

HEALTH , SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.basf.us, e-mailing your request to basfbscst@basf.com or calling 1(800) 433-9517. Use only as directed. For medical emergencies only, call ChemTrec® 1(800)424-9300.

LIMITED WARRANTY NOTICE

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. **BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS.** The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is the replacement of product or refund of the purchase price, at the sole option of BASF. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. **BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.**

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.